

LOGLIFE matt



Sustainable development and production



EMAS:

- Continuous improvement of environmental performance
- Annual sustainability report
- Energy and water management
- Social Fairness



DIN ISO 14001:

- Continuous improvement in reducing waste and CO2 emissions, and saving of energy, water and material consumption



ISO 50001:

- Continuous improvement of energy management: performance, efficiency, security, use and consumption



A.I.S.E.-Charter:

- Safe and sustainable manufacturing of cleaning products



DIN ISO 9001:

- Continuous improvement of management processes and customer satisfaction
- Established quality management system in product development and production

green-Effective® High-performance matt floor polish

■ Eco-efficient performance with eco-effective product design

User and environmental safety at the highest cleaning performance



- Developed to fulfil the Austrian Ecolabel
- Complete abandonment of toxic and harmful materials
- Outperforms other products at lower use concentration

Intensive use of renewable resources – continuous increase of the reutilisation score



- Production under extensive use of renewable raw materials and energy using to 100% hydroelectric, solar and geothermic power
- Active water stewardship maintaining an own fresh and waste water treatment

Ingredient declaration

For the ingredients list, please see the Safety Data Sheet

Traditional German quality - driving your durable business development



- More than 30 years pioneer in sustainable product development
- Smart hygiene solutions ensuring profitable growth
- Trusted brand

Professional user training and on-site support for Sustainable Hygiene Solutions



- Comprehensive knowledge transfer through qualified cleaning consultants
- Customized hygiene plans and cleaning recommendations optimizing your business and cleaning procedures
- Increased service value and strengthened company reputation



makes the difference

LONGLIFE matt



green-Effective® High-performance matt floor polish

■ Resistant ■ Matt appearance ■ High-quality care protection

Product profile

- LONGLIFE matt is a high-performance dispersion providing excellent results.
- LONGLIFE matt is also a high-quality care protection for real-wood floorings which produce resistant protection layer in order to extend the surface lifespan.
- LONGLIFE matt ensures outstanding durability, and resistance thanks to special developed technology.
- The use of special polymers prevents clouding of protective film after maintenance cleaning.
- The product preserves the surface and it delays a renovation with elaborate grinding work.
- Thanks to a very good alcohol, and disinfectant resistance as well as slip-resistance (certified in accordance with DIN 18032-2), LONGLIFE matt is particularly suitable for use in health facilities, and wherever a matt appearance is required.
- Protective film provided by LONGLIFE matt ensures outstanding resistance while having highly elastic properties, and extraordinary adherence on all flooring types.
- Owing its special characteristics LONGLIFE matt can also be applied on residual damp linoleum floors. A renewal of protective film is possible without significant increase of gloss level.
- This product works ideally in a system with LINAX complete, which easily removes LONGLIFE matt polymer films.
- By the complete abandonment of hazardous ingredients such as zinc, TBEP, perfume, and fluorinated levelling agents, LONGLIFE matt takes on the responsibility for future generations.

Area of application

- LONGLIFE matt is suitable for universal use on all coatable flooring especially elastic flooring made of PVC, linoleum, natural rubber and other special synthetic materials.
- It can be even used on oiled and lacquered wood, such as oak, beech, spruce as well as for massive and finished parquet.
- Specially recommended for highly frequented areas, e.g. hospitals, nursing home, medical practice etc., where semi matt coatings with high durability and high slip resistance are required.
- Not to be used on polished stone floors, stoneware tiles, as well as on unsealed wood.
- It can be also used for floorings which have been primed with TIMBER natura.

Product safety, storage and environmental instructions

Safety: For professional use only. Do not mix with other products. Test material compatibility before use. For further information, see Safety Data Sheet.

Storage: Store at room temperature in the original container. The storage and transport temperature of LONGLIFE matt must not exceed 30°C. Keep from freezing.

Environmental: Only give completely emptied packaging in the recommended waste container.

Application and Dosing



Dose in relation to application. Follow below instructions.



Shake before use.

concentrated



Floor preparation: strip the floor, remove all dirt and old dispersion or care layers.



Initial treatment: apply 2-3 thin and uniform layers. Drying time between the applications at least 30min.



Large areas: work in sections and apply wet in wet. Usage: approx. 2 L / 100 m².

200 ml/L



Coating refreshment: remove slight scratches using the spray-cleaner-method and a highspeed machine with red pad.



Care film refreshment for wooden floor: spray on the floor and treat with a single disk machine and a standard blue pad.

Sales units

Order No. 714289 2 x 5 L

Your trusted partner on site

IVEC
PRODAJA, SERVIS: +386 (0) 2 22 96 700

pH-Value

